


**PRODUCT LEGEND**

1	INLET NIPPLE (1" FPT)
2	NUT
3	ISOLATION RING
4	COLLAR / WELD FITTING
5	STAINLESS STEEL FLEXIBLE BRAIDED HOSE (1" NOMINAL DIAMETER) (AH2) (LENGTHS AVAILABLE 31", 36" 48", 60", & 72")
6	COLLAR / WELD FITTING
7	NUT
8	V36 DRY SPRINKLER ASSEMBLY
9	NUT
10	LOCK WASHER
11	BASE PLATE
12	RUBBER PLUG
13	VIC MECHANICAL-T OUTLET STYLE 922 FIRELOCK (1" FMPT) SEE VICTAULIC SUBMITTAL NUMBER 10.90



SEE SUBMITTAL 10.90 FOR  
MAXIMUM TOTAL BENDS



**NOTES:**  
1. REFER TO VICTAULIC SUBMITTAL 10.90 FOR  
ADDITIONAL DETAILS.

**BRAIDED VICFLEX FLEXIBLE  
HOSE SPRINKLER ASSEMBLIES  
FOR DRY PENDENT SPRINKLERS**

		CONSTRUCTION PIPING SERVICES DIVISION	
PROJECT:	_____	PROJ.#	_____
CUSTOMER:	_____	P.O.#	_____
SYSTEM: VICFLEX SERIES AB6 BRACKET FOR DRY PENDENT SPRINKLERS			
REF. DWG.: VICTAULIC SUBMITTAL 10.90			
DRN.BY: RGS	DATE: 02/11/13	DRAWING NUMBER	REV.
CHK.BY: .	DATE: .	VICFLEX-B-FFP	D